





Compact Track Loader

Do more

The ST50 is the largest and most powerful track loader in the Wacker Neuson lineup. Equipped with a 75 kW Kohler engine, making 490 Nm of torque, this machine is a productive workhorse. The extra power enhances the auxiliary flow for improved performance with high flow attachment applications like cold planning and brush clearing.



Highlights

- Controls for Every Operator
- Two-speed transmission
- 5.7-inch Color Display
- Forward Tipping Cab
- Maximum Visibility

Technical Data


Hydraulic


Flow rate	95.0 l/min	
Flow rate max.	141.0 l/min	
Auxiliary hydraulics relief pressure	275.0 bar	
Mechanical - Output Details		
Ground Pressure	0.3 bar	
Breakout force - tilt	42,761.0 N	
Breakout force - lift	42,276.0 N	
Tractive Effort max. at 100% effective force	55,970.0 N	
Travel speed stage 1	10.0 km/h	
Travel speed stage 2	16.0 km/h	
Engine		
Cooling	Water-cooling	
Engine type	Diesel engine	

Cylinder	4.0
Cylinder capacity	3,400.0 cm3
Oil filling max.	15.6
Operating power	75.0 KW
Operating Engine speed	2,500.0 1/min
Battery capacity (nom. value)	950.0 Ah
Engine Manufacturer	Kohler
Operating Fluids	
Hydraulic fluid volume	40.0
Fuel Tank capacity	133.0 I
Chassis	
Tip Load	4,536.0 kg
Rated Operating Capacity at 35% Tip Load	1,588.0 kg

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes

Dimensions





A1	Overall length with bucket	3,794 mm
B1	Overall length without bucket	3,048 mm
C1	Overall width with bucket	2,045 mm
C2	Overall width without bucket	1,982 mm
D1	Overall height	2,150 mm
F1	Hinge pin height	3,463 mm
G1	Dump height max.	2,755 mm
H1	Dump angle	40 °
l1	Bucket rollback at max. stroke height	94 °
J1	Dump reach	926 mm
L1	Ground clearance	272 mm
M1	Angle of departure	30 °
E1	Length of track on ground	1,683 mm
K1	Bucket rollback at ground level	30 °