

PS2-3703

Submersible Pump

powerful and reliable for construction site dewatering

The robust PS series three-phase submersible pumps can handle wastewater containing solids up to a diameter of 20 mm. They feature a high flow rates and high heads, making them ideal for applications where it is important to dry out construction sites quickly and reliably. These high-quality pumps are extremely durable and easy to use. The PS series are also offered in lightweight aluminum models and automatic versions.

Highlights

- Model variations
- Optional motor protection plug for three-phase pumps
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Safe to run dry

Technical Data

Electrical - Output Details

Nominal current	7.70 A
Nominal voltage	400.0 V
Nominal frequency	50.0 Hz
Phase	3.0 ~

Mechanical Details

Length	235.0 mm
Width	215.0 mm
Height	570.0 mm
Operating weight	62.0 kg
Intake-/Pressure socket-dia.	50.0 mm

Motor

Nominal speed	2,860.0 1/min

Electrical System

Length Cable	20.0 m
Cable cross-section	1.5 mm²

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com