

IRFU45/120/5 UK

High-frequency internal vibrators

Top Performance from every model

The IRFU high-frequency internal vibrator series are easy to use. They simply connect to the single-phase power supply and are ready to use. They offer reliable operation even when used with fluctuating generator input voltages. The Wacker Neuson IRFU high-performance internal vibrator is designed for long life and professional concrete consolidation results. It is available in many different versions. The integrated personal protection switch (Bodyguard™) offers a high standard of safety.

Highlights

- Bodyguard
- Completely tempered vibrator head
- Thermal overload protection breaker
- High-performance electric motor with stable speeds
- Switch box with integrated frequency converter

Technical Data

Electrical - Output Details

Nominal current	9.60 A
Nominal voltage	110.0 - 130.0 V
Nominal frequency	50.0 - 60.0 Hz
Nominal power [P]	0.88 kW
Phase	1.0 ~

Mechanical - Output Details

Amplitude at air	2.300 mm
Vibrations	12,000.0 1/min
Vibrations (Hz)	200.0 Hz

Mechanical Details

Head diameter/-diagonal	45.0 mm
Length Hose	5.0 m
Weight	17.00 kg
Rubber cap	no

Motor

Motor type	Asynchronous motor

Environment Data

Protection class	I / Protective earthing
Degree of protection	IP67

Electrical System

Breaker Switch On/Off	Yes
Integrated transformer	yes
Length Cable	15.0 m
Kind of plug	CEE-Plug 2P+E 16A 110V 4H

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com