



PST3 750

Submersible Pump

Durable, lightweight and perfect for any job

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Highlights

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

■ Mechanical - Output Details

Flow rate max.	240.0 l/min
Solid diameter max.	6.0 mm
Delivery height max.	12.0 m

Nominal frequency 60.0 Hz

Nominal speed 3,408.0 1/min

■ Mechanical Details

Length	317.0 mm
Width	185.0 mm
Height	388.0 mm
Operating weight	19.0 kg
Intake-/Pressure socket-dia.	80.0 mm

Nominal frequency 60.0 Hz

■ Environment Data

Temperature limit borrowed liquid 40.0 °C

■ Motor

Nominal power	0.75 KW
Nominal current	10.0 A
Nominal voltage	110.0 V

■ Electrical System

Length Cable 10.0 m

Cable cross-section 2.0 mm²

Cable definition PVC Sheath

■ Shipping and Storage

Length for shipping 483.0 mm

Width for shipping 330.0 mm

Height for shipping 260.0 mm

Shipping weight 21.9 kg