



## PST3 750

### Submersible Pump

Durable, lightweight and perfect for any job

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

## Highlights

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

## Technical Data

### ■ Mechanical - Output Details

|                      |             |
|----------------------|-------------|
| Flow rate max.       | 240.0 l/min |
| Solid diameter max.  | 6.0 mm      |
| Delivery height max. | 12.0 m      |

### ■ Mechanical Details

|                              |          |
|------------------------------|----------|
| Length                       | 317.0 mm |
| Width                        | 185.0 mm |
| Height                       | 388.0 mm |
| Operating weight             | 19.0 kg  |
| Intake-/Pressure socket-dia. | 80.0 mm  |

### ■ Motor

|                 |         |
|-----------------|---------|
| Nominal power   | 0.75 KW |
| Nominal current | 10.0 A  |
| Nominal voltage | 110.0 V |

|                   |               |
|-------------------|---------------|
| Nominal frequency | 60.0 Hz       |
| Nominal speed     | 3,408.0 1/min |

### ■ Environment Data

|                                   |         |
|-----------------------------------|---------|
| Temperature limit borrowed liquid | 40.0 °C |
|-----------------------------------|---------|

### ■ Electrical System

|                     |                     |
|---------------------|---------------------|
| Length Cable        | 10.0 m              |
| Cable cross-section | 2.0 mm <sup>2</sup> |
| Cable definition    | PVC Sheath          |

### ■ Shipping and Storage

|                     |          |
|---------------------|----------|
| Length for shipping | 483.0 mm |
| Width for shipping  | 330.0 mm |
| Height for shipping | 260.0 mm |
| Shipping weight     | 21.9 kg  |