

AR26/6/042 3,5kN

External vibrators for consolidation of in-situ concrete

Quality exposed concrete surface is first-rate

For the production of concrete surfaces, flawlessly consolidated concrete is essential. The high quality design of Wacker Neuson's AR26 external vibrator offers precision concrete consolidation. The result: beautifully smooth and level concrete surfaces on walls, pillars and columns.

Highlights

- Small, compact and light
- Asynchronous motor with stable speed
- Sturdy design

Technical Data

Electrical - Output Details

Nominal current	8.00 A
Nominal voltage	42.0 V
Nominal frequency	200.0 Hz
Nominal power [P]	0.30 kW
Phase	3.0 ~

Mechanical - Output Details

Centrifugal force	3 kN
Vibrations	6,000.0 1/min
Vibrations (Hz)	100.0 Hz
Centrifugal force max.	3.47 kN

Mechanical Details

Length	223.0 mm
Width	190.0 mm
Height	102.0 mm
Weight	6.46 kg
Unbalanced mass/side pos1	8.0
Unbalanced mass/side pos2	0.0
Hole pattern length	9.0 mm
Hole pattern width	125.0 mm
Hole pattern hole diameter	12.0 mm

Motor

Motor type	Asynchronous motor

Environment Data

Protection class	III / Safety extra-low voltage
Degree of protection	IP67

Electrical System

Breaker Switch On/Off	no
Operating indicator	yes
Adjusting frequency	No
Integrated transformer	No
Length Cable	10.0 m
Kind of plug	CEE-Plug 3P 32A 42V 4H

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com