



DPU 3050H US

Reversible vibratory plate

Maximum compaction in the tightest spaces

The DPU3050H is one of the powerful all-rounders for paving work, gardening and landscaping, as well as for maintenance work on roads, paths and parking lots. Like all vibratory plates in the 25 - 37 kN class from Wacker Neuson, it features a robust, integrated wheel set. As a result, this class of equipment offers mobility on the construction site that is unique in the market. Due to its compact design and great maneuverability, the DPU3050H is ideal for compacting trenches, sidewalks and other confined areas. Well thought-out details make it the ideal compactor for continuous professional use.

Highlights

- Compact dimensions, high performance
- Integrated wheel set
- Sturdy and durable

Technical Data

Mechanical - Output Details

Centrifugal force	30 kN
Area capacity	570.0 m2/h
Forward Running	19.0 m/min
Gradeability	46.6 %
Vibrations (Hz)	90.0 Hz
Mechanical Details	
Mechanical Details Length Baseplate	703.0 mm
	703.0 mm 500.0 mm
Length Baseplate	

Height Cover frame	777.0 mm
Thickness Baseplate	10.0 mm
On avating variable	101.0 km
Operating weight	181.0 kg
Ground clearance	777.0 - 887.0 mm
Circuita clearance	777.0 - 807.0 111111
Engine	
Effective power	4.2 KW
Lifective power	4.2 1000
Nominal Engine speed	2,800.0 1/min
rtorima Engine opeca	2,000.0 1/111111
Environment Data	
LIAV average tion (average value)	0.0/-0
HAV summation (average value)	3.6 m/s2
HAV summation (Standard)	EN 500-4
TIAV Sullillation (Standard)	LIN 300-4