



**WACKER
NEUSON**
all it takes!

PS2-1503

Submersible Pump

powerful and reliable for construction site dewatering

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Highlights

- Model variations
- Optional motor protection plug for three-phase pumps
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Oil lifter for reliable lubrication in any situation
- Safe to run dry
- Steel sleeve reduces wear of the shaft

Technical Data

■ Electrical - Output Details

| | |
|-------------------------------|---------|
| Nominal voltage | 400.0 V |
| Nominal frequency | 50.0 Hz |
| Starting current Idle running | 20.0 A |
| Starting current full load | 3.4 A |
| Phase | 3.0 ~ |

■ Mechanical - Output Details

| | |
|----------------------|-------------|
| Flow rate max. | 430.0 l/min |
| Solid diameter max. | 8.5 mm |
| Delivery height max. | 21.5 m |

■ Mechanical Details

| | |
|------------------------------|----------|
| Length | 235.0 mm |
| Width | 215.0 mm |
| Height | 550.0 mm |
| Operating weight | 29.0 kg |
| Intake-/Pressure socket-dia. | 50.0 mm |

■ Motor

| | |
|---------------|---------------|
| Nominal speed | 2,850.0 1/min |
|---------------|---------------|

■ Electrical System

| | |
|---------------------|---------------------|
| Length Cable | 20.0 m |
| Cable cross-section | 1.5 mm ² |