



DPU 3750Hets

Reversible vibratory plate

Maximum compaction in the tightest spaces

The lightweight reversible vibratory plates are powerful and versatile making them ideal for base preparation, gardening, landscaping and maintenance work on streets, roads and parking lots. The Wacker Neuson vibratory plates in the 25-37 kN class come equipped with a sturdy, integrated wheel set. This unique feature provides mobility on the construction site.

Highlights

- Compact dimensions, high performance
- Integrated wheel set
- Sturdy and durable

Technical Data

■ Mechanical - Output Details

Centrifugal force	37 kN
Area capacity	720.0 m ² /h
Forward Running	24.0 m/min
Gradeability	46.6 %
Vibrations (Hz)	90.0 Hz

■ Mechanical Details

Length Baseplate	703.0 mm
Width	500.0 mm
Width Baseplate	500.0 mm
Height	1,101.0 mm

Height Cover frame	777.0 mm
Thickness Baseplate	10.0 mm
Operating weight	265.0 kg
Underclearance	777.0 - 887.0 mm

■ Engine

Effective power	4.2 kW
Nominal Engine speed	2,800.0 1/min

■ Environment Data

HAV summation (average value)	2.5 m/s ²
HAV summation (Standard)	• EN 500-4

Available engines

■ Hatz 1B30-2-311A

Cooling	air cooling
Engine type	Diesel engine
Engine operating mode	four-stroke
Cylinder	1
Cylinder capacity	347 cm3
Fuel	Diesel EN 590
Fuel consumption	0.60 l/h
Tank capacity	5.00 l
Starter type	Recoil starter
Engine Manufacturer	Hatz