



HI1000

Indirect Fired Air Heaters

large air heater for the harshest applications

The HI1000 is Wacker Neuson's highest capacity indirect fired air heater. Available with or without a fuel tank. For remote applications, our DGM version includes a custom extended service genset. All versions are ETL certified.

Highlights

- Cold Weather Ready
- Digital control panel

Technical Data

■ Electrical - Output Details

| | |
|-------------------|---------|
| Nominal current | 30.00 A |
| Nominal voltage | 230.0 V |
| Nominal frequency | 60.0 Hz |
| Phase | 1.0 ~ |

■ Mechanical Details

| | |
|--|------------|
| Length | 3,034.0 mm |
| Width | 1,186.0 mm |
| Height | 1,707.0 mm |
| Lift Bail - quantity | 1.0 |
| Duct Length max., 3x12" Supply Adapter | 30.0 m |
| Duct Length max., 2x16" Supply Adapter | 30.0 m |
| Duct Length max., 1x20" Supply Adapter | 61.0 m |

Duct Length max., 1x20" Return Adapter 15.0 m

■ Generator

| | |
|--------|----|
| Genset | no |
|--------|----|

■ Environment Data

| | |
|-----------------|------------|
| Sound level LpA | 77.6 dB(A) |
|-----------------|------------|

■ Electrical System

| | |
|---------------------|---------|
| Temperature monitor | digital |
|---------------------|---------|

■ Operating Fluids

| | |
|------------------------------|-------------|
| Fuel Consumption Natural Gas | 401.1 l/min |
|------------------------------|-------------|

■ Shipping and Storage

| | |
|---------------------|------------|
| Length for shipping | 3,270.0 mm |
| Width for shipping | 1,042.0 mm |
| Height for shipping | 1,732.0 mm |