



PSR1 500

Submersible Pump

These high performance single-phase submersible pumps are ideal for job sites needing fast, dependable, low level water pumping.

Pump can start in low water levels when it is primed through the discharge port. No matter how large or small the job. Wacker Neuson submersible pumps offer the versatility and durability contractors need for light dewatering. Suitable for most outlets, these pumps offer big pump features for small pump investment.

Highlights

- Built-in thermal protection prevents motor damage
- Top discharge for continuous operation and motor cooling
- Kink-free multi-directional discharge coupling

Technical Data

■ Mechanical - Output Details

| | |
|----------------------|-------------|
| Flow rate max. | 310.0 l/min |
| Solid diameter max. | 6.0 mm |
| Delivery height max. | 18.0 m |

■ Mechanical Details

| | |
|------------------|----------|
| Length | 192.0 mm |
| Width | 223.0 mm |
| Height | 341.0 mm |
| Operating weight | 13.8 kg |

■ Motor

| | |
|---------------|---------|
| Nominal power | 0.75 KW |
|---------------|---------|

| | |
|-------------------|---------------|
| Nominal frequency | 60.0 Hz |
| Nominal speed | 3,300.0 1/min |

■ Electrical System

| | |
|--------------|--------|
| Length Cable | 15.0 m |
|--------------|--------|

■ Shipping and Storage

| | |
|---------------------|----------|
| Length for shipping | 475.0 mm |
| Width for shipping | 267.0 mm |
| Height for shipping | 260.0 mm |
| Shipping weight | 17.0 kg |