



## 8115

### Wheel loaders

#### THE ROBUST HIGH-PERFORMANCE WHEEL LOADER

The Kramer wheel loader 8115 is among the premium range of the 8 series and is equipped with the proven principle of the one-piece vehicle chassis. The bucket volume of 1.15 m<sup>3</sup> to 1.8 m<sup>3</sup>, depending on the material density, paired with the unique, powerful engine options, makes the 8115 one of the real high-performance wheel loaders. The optionally available ecospeed transmission and the large tires make diverse applications a possibility with this machine.

**Fuel saving:** By selecting the correct operating mode of the four available (Power, Eco, Road, CSD), it is possible to save up to 10% fuel

**7-inch LCD display:** The optional 7" display provides assistance systems and versatile application options, like joystick sensitivity and angle display

**Increased lift height:** The optionally long loading unit enables more in terms of loading and stacking heights

**Smart Attach:** The fully-hydraulic quickhitch plate, installed as standard, makes it possible to comfortably hitch up hydraulic attachments without needing to exit the machine

**24-Inch tires:** Excellent smooth running, best traction, and optimal sustainability

## Technical Data

### Standard engine data

Engine manufacturer	Deutz
Drive output	55.4 kW
Drive output	75 PS
Cylinder capacity	2,924 cm <sup>3</sup>
Exhaust standard level	V
Exhaust aftertreatment	DOC / DPF

### Weights

Bucket capacity (standard bucket)	1.15 m <sup>3</sup>
Payload (max.)	2,070 kg
Operating weight	5,700 - 6,500 kg
Payload (S=1.25)	2,900 kg
Tipping load (standard bucket)	4,250 kg
Tipping load (pallet fork)	3,625 kg

### Filling levels

Tank capacity for fuel	120 l
Tank capacity for hydraulic oil	64 l

### Drive system

Travel speed Standard	0-20 km/h
Travel speed Option 1	0-30 km/h
Travel speed Option 2	0-40 km/h
Differential lock	100 % front axle + rear axle

### Hydraulic system

Work hydraulics discharge volume (max.)	80 l/min
---	----------

### Kinematics

Kinematics type	P
Quick change system	Kramer HV/WL-L; includes Smart Attach

### Steering

Steering angle max.	40 degree
---------------------	-----------

### Noise characteristic values

Guaranteed sound power level L <sub>WA</sub> (cabin)	101 dB(A)
Measured sound power level L <sub>WA</sub>	98.8 dB(A)
Sound pressure level at the operator's ear	74 dB(A)

## Dimensions



A1	Total length with standard attachment	5,878 mm
A2	extended loading system	5,878 mm
B1	Wheel base center	2,150 mm
C1	Rear overhang	1,620 mm
D3	Height with cab	2,690 mm
D6	Height with air-conditioning system	2,775 mm
D8	Height with panoramic cab	2,730 mm
D9	Height with panoramic cab and air-conditioning system	2,775 mm
D10	Total height with rotating beacon	2,965 mm
E1	Max. height blade pivot point	3,450 mm
E2	Max. height of hinge pin height extended loading system	3,680 mm
F1	Load-over height	3,200 mm
F2	extended loading system	3,470 mm
G1	Dumping height	2,650 mm
G2	extended loading system	2,990 mm
H1	Dumping width	660 mm
H2	extended loading system	450 mm
I1	Digging depth	95 mm
J1	Total width	1,970 mm
K1	Ground clearance	390 mm
L1	Turning radius outer edge wheels	3,000 mm
M1	Steering angle	40 °
M2	Swing angle	22 °
N1	Dumping angle at max. lifting height	45 °
O1	Dumping angle at ground level	50 °
P1	Distance center front axle to tooth tip	2,120 mm
Q1	Bucket width	2,150 mm
R1	Stacking height	3,280 mm
R2	extended loading system	3,510 mm

## Standard components

### Cab

- Soundproofed, vibration-insulated, 4-point cab with large, thermal insulation glazing deep-drawn and rear window heating
- Entry and exit on both sides
- Comfort seat with mechanical suspension (MSG85/722), with automatic seat belt, weight, backrest and two-fold horizontal adjustment
- 3-stage powerful heating and ventilation, and defroster nozzles on the front windscreen
- Colour-coded rocker switch for hydraulic, electric, driving and safety features
- Telescoping and adjustable tilting steering column
- Joystick console (fold-down)
- Sun visor, interior mirror, 12 V plug receptacle, cab light, large, foldable outside rear-view mirror on both sides
- Windscreen wipers front and back, front with intermittent wipers
- Working lights 2x LED basic rear, working lights 2x LED basic front (1000 Lm)
- StVZO (German road traffic regulations) lighting
- Tested according to ROPS and FOPS I

### Engine

- Battery isolator switch
- Hydraulic fan drive
- Engine automatic stop

### Power transmission

- Combined brake-inch pedal
- Connectible 100% lock differential in front and rear axle
- Mechanical parking brake
- Lubrication line for pendulum pins

### Steering and work hydraulics

- Hydrostatic all-wheel steering with emergency steering properties
- Electronic pilot-operated joystick for lifting / lowering and filling / emptying the loader unit with rocker switch for selecting the travel direction as well as integrated 3rd control circuit (proportional control) and functional lighting integrated into the joystick
- Pressure release of 3rd control circuit

### Kinematics

- Smart Attach (fully-hydraulic quickhitch facility)
- Parallel kinematics
- Load hook on the tilt rod
- Visual position display for bucket and fork

### Documentation

- Operator's manual, service manual

## Options

### Operator's cab & Cabine

- Cab with sliding window in left-side door glass
- Panoramic cab
- Air-sprung operator's seat with lumbar support and heated seat (MG95AL/722)
- Auxiliary heating
- Exterior mirrors, right and left heated
- Air-conditioning system
  - only in combination with:
    - Panoramic cab
- Document box
- Radio DAB+ ready (antenna, speaker)
- Radio system DAB+ reception (BT radio, antenna, speaker)
- 7" display + jog dial (incl. angle display, oil volume adjustment, automatic load stabilizer setting, tractive force regulation, joystick sensitivity)
- Bracket for cell phone + USB outlet
- Rear-view camera
  - only in combination with:
    - 7" display + jog dial (incl. angle display, oil volume adjustment, automatic load stabilizer setting, tractive force regulation, joystick sensitivity)

## Lighting

- LED rotating beacon
- 4x LED Basic work lights at the front (1000 Lumen)
- 2x LED Basic work lights side-mounted (1000 Lumen)

## Approval, road traffic

- License plate bracket (incl. license plate illumination)
  - includes:
    - License plate illumination
    - License plate bracket, front and rear
- Sidelights for special buckets incl side marker lights
- Data confirmation (ABE) for self-propelled work machine (standard)\*
- EC Tractor CoC for Agricultural/Forestry Tractor Approval (LOF-ZGM-EG-Zulassung, 2003/37/EC – Class T1)
  - only in combination with:
    - License plate bracket (incl. license plate illumination)
    - Rear outlet 7-pole
    - An attachment coupling (not maneuvering hitch) must also be selected!
- EC Tractor CoC for Agricultural/Forestry Tractor Approval (LOF-ZGM-EG-Zulassung, 2003/37/EC – Class T1) + data confirmation – only for Germany
  - only in combination with:
    - License plate bracket (incl. license plate illumination)
    - Rear outlet 7-pole
    - An attachment coupling (not maneuvering hitch) must also be selected!

\*Germany, Luxembourg, Netherlands, Austria, Slovakia, the Czech Republic, Switzerland, Estonia, Latvia, Lithuania, Hungary

## Drive system & steering

- Motor with increased power (Deutz TCD 3.6 74 kW / 100 hp) – exhaust emission Stage V
- Reversible fan motor
- Automatic engine stop (standard)
- Ecospeed 40 km/h incl. Smart Driving
  - only in combination with:
    - Motor with increased power (Deutz TCD 3.6 74 kW / 100 hp) – exhaust emission Stage V
    - License plate bracket (incl. license plate illumination)
    - Load stabilizer (vibration damper)
- Ecospeed 40 km/h incl. Smart Driving (limited to 30 km/h)
  - only in combination with:
    - Motor with increased power (Deutz TCD 3.6 74 kW / 100 hp) – exhaust emission Stage V
    - License plate bracket (incl. license plate illumination)
    - Load stabilizer (vibration damper)
- Ecospeed 40 km/h incl. Smart Driving (limited to 20 km/h)
  - only in combination with:
    - Motor with increased power (Deutz TCD 3.6 74 kW / 100 hp) – exhaust emission Stage V
    - License plate bracket (incl. license plate illumination)
    - Load stabilizer (vibration damper)
- Ecospeed 30 km/h incl. Smart Driving
  - only in combination with:
    - License plate bracket (incl. license plate illumination)
    - Load stabilizer (vibration damper)
  - not with
    - Motor with increased power (Deutz TCD 3.6 74 kW / 100 hp) – exhaust emission Stage V
- Driving mode Power/Eco/Road/Pedal mode (incl. low-speed control & manual throttle)
- Steering type Smart Steering
  - only in combination with:
    - 7" display + jog dial (incl. angle display, oil volume adjustment, automatic load stabilizer setting, tractive force regulation, joystick sensitivity)

## Tires

Not possible with EC Tractor CoC for Agricultural/Forestry Tractor Approval (LOF-ZGM-EG-Zulassung, 2003/37/EC – Class T1)

- Mitas 405/70 R24 EM 01 – multi-purpose profile, direction-independent

## Tires for EC tractor

Required for EC Tractor CoC for Agricultural/Forestry Tractor Approval (LOF-ZGM-EG-Zulassung, 2003/37/EC – Class T1)

- Mitas 16/70-20 MPT-04 ET0 – construction machine profile
- Mitas 405/70-24 MPT-04 – construction machine profile (standard)
- Michelin 400/70R20 BIBLOAD – multi-purpose profile
- Michelin 400/70 R24 XMCL ET0
- Nokian 420/65 R24 TRI 2 – municipal profile (caution: no digging depth / reduced steering angle)
- Firestone 400/70 R20 Duraforce
- Trelleborg 400/70R20 TH500 ET0
- Trelleborg 400/70R20 TH400 ET0
- Trelleborg 400/70R24 TH400 ET0

## Loading system & Quick coupler system

- Load stabilizer (vibration damper)
- Loading system with increased lift height (payload and bucket volume reduced)
- Floating position
- Smart Attach (fully hydraulic quick coupler system); Kramer System HV/WL-L (standard)
- Hydraulic quick coupler system, Volvo "Z" System (technical data and available attachments may differ)
  - not with:
    - Loading system with increased lift height (payload and bucket volume reduced)

## Hydraulics

- Pre-heating package
  - includes:
    - Hydraulic oil pre-heating (230 V)
    - Coolant pre-heating (230V)
    - Fuel pre-heating (230 V)
- Filling of the hydraulic system with environmentally friendly and biodegradable hydraulic oil

## Hydraulics - front area

- Front return line, unpressurized return + leak oil
- High flow; incl. 1 double-acting control circuit for positioning movements with attachment, incl. leak oil line and unpressurized return
  - Recommended:
    - Front outlet 7-pole (2 switch positions)
    - Driving mode Power/Eco/Road/Pedal mode (incl. low-speed control & manual throttle)
- Automatic bucket return
  - only in combination with:
    - 7" display + jog dial (incl. angle display, oil volume adjustment, automatic load stabilizer setting, tractive force regulation, joystick sensitivity)
- Shake function (vibratory function of the tipping cylinder)
  - only in combination with:
    - Automatic bucket return
    - 7" display + jog dial (incl. angle display, oil volume adjustment, automatic load stabilizer setting, tractive force regulation, joystick sensitivity)
- 4th control circuit for front add-on equipment with 2nd hydraulic function, proportional
- Tipping cylinder and lowering throttle for work platform preparation (ex-factory only, not retrofittable)
  - only in combination with:
    - Hose burst valve for lifting and tilting cylinders

## Hydraulics - rear area

- Auxiliary control circuit for tipper (tipper connection)
- Auxiliary control circuit for tipper (for rear attachments, single-acting) including unpressurized return

## Electrical system

- Rear outlet 7-pole
- Rear outlet 13-pole
- Front outlet 7-pole (2 switch positions)
- Rear outlet (DIN signal socket)
- Front outlet (30A)

## Safety options

- Hose burst valve for lifting and tilting cylinders
- Reverse alarm (acoustic)
- Red/white warning stripes (in accordance with DIN 30710)
- EquipCare + Dual ID
  - not with:
    - Immobilizer system, integrated in the ignition switch key
- Immobilizer system, integrated in the ignition switch key
  - not with:
    - EquipCare + Dual ID
- Fire extinguisher (2 kg)
- Seatbelt monitoring with seatbelt alarm
- Orange safety belt (standard)
  - not with:
    - Air-sprung operator's seat with lumbar support and heated seat (MG95AL/722)

## Paint

- Single-color RAL custom paint finish (gray parts not included)\*\*
- Vehicle operation with corrosive agents (salt and fertilizer use)

\*\* We reserve the right to decline paint finishes that exhibit similarities to protected colors or color combinations of other manufacturers!

## Other

- (Fully automatic) central lubrication unit
  - not with:
    - Vehicle operation with corrosive agents (salt and fertilizer use)
- Central lubrication system (corrosive agents)
  - recommended with:
    - Vehicle operation with corrosive agents (salt and fertilizer use)
- Central lubrication point

## Ball hitches & Brake systems

- Ball hitch attachment coupling (K50) – fixed to frame
- Automatic attachment coupling 38 mm – fixed to frame
- Mechanical attachment coupling 38 mm – fixed to frame
- Bearing block for attachment couplings height-adjustable (insert for attachment coupling required)
- Automatic 38 mm attachment coupling insert for trailer mount height-adjustable
- K50 ball hitch insert for trailer mount height-adjustable, only suitable for height-adjustable drawbars
- K50 ball hitch insert for trailer mount height-adjustable extended
- Mechanical attachment coupling insert – 32 mm for trailer mount height-adjustable
- Pneumatic trailer brake valve
  - only in combination with:
    - Ecospeed 40 km/h incl. Smart Driving
  - or
    - Ecospeed 40 km/h incl. Smart Driving (limited to 30 km/h)
  - or
    - Ecospeed 40 km/h incl. Smart Driving (limited to 20 km/h)
- Hydraulic trailer brake valve
  - only in combination with:
    - Ecospeed 40 km/h incl. Smart Driving
  - or:
    - Ecospeed 40 km/h incl. Smart Driving (limited to 30 km/h)
  - or:
    - Ecospeed 40 km/h incl. Smart Driving (limited to 20 km/h)

A front ballast weight is required to operate a trailer with the corresponding bearing load.

## Extended warranties

- Security 24 (2000 h)
- Security 36 (3000 h)
- Security 48 (4000 h)
- Security 60 (5000 h)