

Vibrators

External





Concrete in all forms

At Wacker Neuson, we offer a wide selection of powerful external vibrators with various speed and operating voltage versions.



Qualty concrete consolidation

Consolidating concrete in-situ or precast elements, as well as separating or loosening material are among the many applications for an external vibrator.

Performance

 Due to the stable speed and powerful electric motor, the machine delivers reliable performance under continuous use

Efficiency

 The compact and lightweight construction of the housing make the external vibrator quick and easy to mount

Maintenance

 The external vibrator is equipped with lifetime lubricated bearings and is completely maintenance-free



Performance Data

	Unit	AR26/6/042	ARFU 26/6/12 0
Vibrations	rpm	6,000	6,000
Max. centrifugal force	lbf	780	780
Rated voltage	v	42,3 ~	110
Rated current	Α	8.0	12
Weight	lb	16.53	24.7
Fastening	mm	90 x 125	90 x 125

Fasteners*

rasteners	Unit	SV4	SV4L	SV5	SV53	SV54
Length	in	12.8	16.5	15.2	15.3	16.1
Width	in	7.7	7.7	7.7	8.1	6.3
Height	in	4.8	4.8	4.8	3.9	8.0
Weight	lb	9.5	12.5	12.1	11.7	13.7

Frequency Converter*

	Unit	FUE6/042/200
Weight	lb	67.2
Input/Output voltage	V	220, 1~ / 42, 3~
Input/Output frequency	Hz	50-60 / 200
Input/Output current	Α	22/50
Power cable	ft	32.8
Receptacles	units	4







