



**WACKER
NEUSON**
all it takes!

IRSE-FU58/230

High-frequency internal vibrators

Concrete consolidation with comfortable operation

The Wacker Neuson IRSE-FU high-frequency internal vibrators have a short protection hose and low vibration handle. The ergonomically designed handle with vibration damping offers a high degree of comfort during operation. Wacker Neuson's IRSEN models/IRSE-FU models of high-quality internal vibrators offer a variety of features and benefits.

Highlights

- Bodyguard
- Handle (Low Vib)
- High-performance electric motor with stable speeds
- Switch box with integrated frequency converter

Technical Data

■ Electrical - Output Details

Nominal current	6.00 A
Nominal voltage	220.0 - 240.0 V
Nominal frequency	50.0 - 60.0 Hz
Nominal power [P]	1.10 KW
Phase	1.0 ~

Weight 17.00 kg

Rubber cap no

■ Motor

Motor type Asynchronous motor

■ Environment Data

Protection class I / Protective earthing

Degree of protection IP67

■ Electrical System

Breaker Switch On/Off Yes

Integrated transformer yes

Length Cable 15.0 m

Kind of plug CEE 7/7 (Plug Type EF)

■ Mechanical - Output Details

Amplitude at air	2.500 mm
Vibrations	12,000.0 1/min
Vibrations (Hz)	200.0 Hz

■ Mechanical Details

Length Hose	0.8 m
-------------	-------