



HI1000

Indirect Fired Air Heaters

large air heater for the harshest applications

The HI1000 is Wacker Neuson's highest capacity indirect fired air heater. Available with or without a fuel tank. For remote applications, our DGM version includes a custom extended service genset. All versions are ETL certified.

Highlights

- Cold Weather Ready
- Digital control panel

Technical Data

■ Electrical - Output Details

Nominal current	30.00 A
Nominal voltage	230.0 V
Nominal frequency	60.0 Hz
Phase	1.0 ~

■ Mechanical Details

Length	119.4 "
Width	46.7 "
Height	67.2 "
Lift Bail - quantity	1.0
Duct Length max., 3x12" Supply Adapter	98.4 Foot
Duct Length max., 2x16" Supply Adapter	98.4 Foot
Duct Length max., 1x20" Supply Adapter	200.1 Foot

Duct Length max., 1x20" Return Adapter 49.2 Foot

■ Generator

Genset	no
--------	----

■ Environment Data

Sound level LpA	77.6 dB(A)
-----------------	------------

■ Electrical System

Temperature monitor	digital
---------------------	---------

■ Operating Fluids

Fuel Consumption Natural Gas	106.0 gal/mi
------------------------------	--------------

■ Shipping and Storage

Length for shipping	128.7 "
Width for shipping	41.0 "
Height for shipping	68.2 "