



GS6503G

Portable Generator of the G series

Reliable power solutions for demanding use

The G Series generators are engineered to meet the demands of professional applications, offering high load starting, high power output, durability and cost-effectiveness. These generators feature with strong air filtration system and a large fuel tank, ensuring longer operation and superior reliability. With a robust frame, the G Series is built to withstand harsh environments and continuous use.

Highlights

- Sturdy protective frame
- Large tank with long running time
- Reliable Loncin engine
- Automatic Voltage Regulation (AVR)
- Compact dimensions

Technical Data

■ Mechanical Details

Length	695.0 mm
Width	546.0 mm
Height	550.0 mm
Dry Weight	82.0 kg

Maximum Output 6,500.0 W

Continuous Output 6,000.0 W

■ Engine

Tank capacity 30.0 l

■ Environment Data

Degree of protection IP23

Sound power LWA, guaranteed 97.0 dB(A)

Sound power LWA (Standard) 2000/14/EG

■ Electrical System

Circuit Breaker Amperage AC 11.0 A

Available voltages 1~ 230.0 V

Breaker Switch On/Off 1 Pole

CE Performance Class G1

Type of battery LiFePO4

Installed capacity 1.6 Ah

Receptacle Type CEE7/3 (Typ F) 2P 16A 250V, IP44 1~

■ Operating Fluids

Fuel consumption (50 % Prime Load) 2.3 L/hr

Run Time (50 % Prime Load) 13.0 hrs