



BPU 2540A US

Reversible vibratory plate

Maximum compaction in the tightest spaces

The lightweight reversible vibratory plates are powerful and versatile making them ideal for base preparation, gardening, landscaping and maintenance work on streets, roads and parking lots. The Wacker Neuson vibratory plates in the 25-37 kN class come equipped with a sturdy, integrated wheel set. This unique feature provides mobility on the construction site.

Highlights

- Compact dimensions, high performance
- Integrated wheel set
- Sturdy and durable

Technical Data

Mechanical - Output Details

Centrifugal force	5,620 lbf
Area capacity	4,908.4 ft ² /h
Forward Running	1.0 fps
Gradeability	36.4 %
Vibrations (Hz)	90.0 Hz

Mechanical Details

Length Baseplate	27.7 "
Width	15.7 "
Width Baseplate	15.7 "
Height	43.2 "
Height Cover frame	26.2 "
Thickness Baseplate	0.4 "

Operating weight	319.7 lb
Underclearance	26.2 - 30.6 "

Engine

Effective power	4.2 hp
Nominal Engine speed	2,800.0 1/min

Environment Data

HAV summation (average value)	8.2 ft/s ²
HAV summation (Standard)	EN 500-4

Electrical System

Coding options	0
Remote Control Range	0.0 Foot

Operating Fluids

Cooling fluid type	0
--------------------	---

Available engines

■ Honda GX160-UH2-QW-X2-SD

Cylinder capacity	9.9 Inch ³
Fuel consumption	0.2 GPH US
Tank capacity	1.0 gal US
Effective power	4.2 PS
Operating power	3.9 PS
Cooling	air cooling
Engine type	Gasoline engine
Engine operating mode	four-stroke
Cylinder	1
Fuel	Gasoline
Standard (Effective power)	ISO 3046 IFN
Standard (Operating power)	ISO 3046 IFN
Starter type	Recoil starter
Engine Manufacturer	Honda