



## IRFU65/120/8 US

### High-frequency internal vibrators

Top Performance from every model

The IRFU high-frequency internal vibrator series are easy to use. They simply connect to the single-phase power supply and are ready to use. They offer reliable operation even when used with fluctuating generator input voltages. The Wacker Neuson IRFU high-performance internal vibrator is designed for long life and professional concrete consolidation results. It is available in many different versions. The integrated personal protection switch (Bodyguard™) offers a high standard of safety.

### Highlights

- Bodyguard
- Completely tempered vibrator head
- Thermal overload protection breaker
- High-performance electric motor with stable speeds
- Switch box with integrated frequency converter

### Technical Data

#### ■ Electrical - Output Details

Nominal current	15.00 A
Nominal voltage	120.0 V
Nominal frequency	50.0 - 60.0 Hz
Nominal power [P]	1.40 KW
Phase	1.0 ~

Weight 30.20 kg

Rubber cap no

#### ■ Environment Data

Protection class	I / Protective earthing
Degree of protection	IP67
Operating temperature range	0

#### ■ Electrical System

Breaker Switch On/Off	Yes
Integrated transformer	yes
Length Cable	14.4 m
Kind of plug	NEMA 5-15P - 14W47

#### ■ Mechanical - Output Details

Amplitude at air	2.500 mm
Vibrations	12,000.0 1/min
Vibrations (Hz)	200.0 Hz

Breaker Switch On/Off Yes

Integrated transformer yes

Length Cable 14.4 m

#### ■ Mechanical Details

Length Hose	8.0 m
-------------	-------

Kind of plug NEMA 5-15P - 14W47