



**WACKER
NEUSON**
all it takes!



HSH3000

Hydronic Surface Heater

Durable and Efficient

The HSH3000 was designed to enhance every aspect of the operator experience featuring a simplified, intuitive two-step start up, centralized controls for effortless operation, and dual reel operations providing worksite efficiency. The compact and lightweight design allow for easy transportation and logistics. The HSH3000 delivers the performance, efficiency, and ease of use all in one smart, powerful package.

Highlights

- Centralized Operations
- Compact Cabinet
- Service Accessibility
- Dual Use Reels
- Two Pump System

Technical Data

Electrical - Output Details

Nominal current	35.00 A
Nominal voltage	120.0 V

Mechanical Details

Length	3,970.0 mm
Gross Axle Weight Rating	2,268.0 kg
Width	2,032.0 mm
Height	2,132.0 mm
Operating weight	3,309.0 kg
Dry Weight	2,637.6 kg
Gross vehicular weight	3,401.0 kg
Length hose	914.0 m

Generator

Output current 1~	35.0 A
Output voltage	120.0 V
Output frequency	60.0 Hz
Voltage Regulation - Steady State	6.0 %
Generator Manufacturer	• Mecc Alte
Generator specification	• Brushless with capacitor
Genset	• yes

Engine

Engine type	• Diesel engine
-------------	-----------------

Cylinder	2.0
Cylinder capacity	700.0 cm³
Operating Engine speed	1,800.0 1/min
Engine Manufacturer	• Rehlko

Operating Fluids

Oil volume	17.000 l
Fuel specification	• Winter Blend Diesel No. 2
Fuel Tank capacity	833.0 l
Fuel Consumption no genset	10.5 l/h
Fuel Consumption with genset	12.2 l/h
Run Time (100 %)	80.0 hrs

Chassis

Brake	• Electric brake
Tires	• 22575R15 D

Shipping and Storage

Length for shipping	3,145.0 mm
Width for shipping	2,033.0 mm
Height for shipping	2,132.0 mm
Shipping weight	2,637.6 kg
Shipping weight with Trailer	2,637.6 kg

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.