



**WACKER
NEUSON**
all it takes!

DT10

Track Dumper



The professional machine

The hydrostatic drive system allows for quick and convenient operation and the single-piece engine hood, as well as the optimal arrangement of the service points, make daily maintenance much easier. The rubber tracks and the excellent weight distribution reduce the ground pressure, ensuring more extensive application uses. The variety of skip versions make it a very versatile machine.

Hydrostatic drive



Simply start and off you go: Because of the hydrostatic drive system, no frequent gear changing is needed and the operator can focus on the task. The hydraulic drive system and the working hydraulics can be operated independently of each other.

Small dimensions



The compact dimensions of the machine make it ideal for manoeuvering and working in confined spaces.



Hanging suspension-mounted rollers

The suspension-mounted rollers provide for a smooth and safer operating experience. Due to the suspended support, the rollers adapt to the terrain and compensate for obstacles or unevenness, such as stones. As a result, the operator benefits from optimal driving comfort, even off-road.

Technical Information

	Units	DT10
Hydraulic		
Hydraulic pump		Variable displacement and gear pump
Flow rate	l/min	66
Mechanical - Output Details		
Travel speed	km/h	4
Mechanical Details		
Length	mm	2,670
Width	mm	830
Height	mm	1,280

Two-cylinder diesel engine

The powerful and lightweight 13-hp diesel engine can accelerate the machine up to the maximum speed.

	Units	DT10
Payload	kg	1,000
Skip capacity heaped	l	427
Operating weight (min.-max.)	kg	665 - 915
Engine		
Motor type		Diesel engine
Effective power	KW	9.6
Nominal engine speed	1/min	3,600
Manufacturer		Kubota
Engine designation		Z-482
Shipping and Storage		
Shipping weight	kg	590

