



## IRSEN58/250GV

### High-frequency internal vibrators

Concrete consolidation with comfortable operation

The Wacker Neuson IRSEN series of high-frequency internal vibrators offer a short protection hose and low vibration handle. The ergonomically designed handle with vibration damping offers a high degree of comfort during operation. Wacker Neuson's IRSEN high-quality internal vibrators offer a variety of features and benefits.

### Highlights

- Handle (Low Vib)
- High-performance electric motor with stable speeds
- Made in Germany
- Sturdy design

### Technical Data

#### Electrical - Output Details

Nominal current	3.00 A
Nominal voltage	250.0 V
Nominal frequency	200.0 Hz
Nominal power [P]	1.05 KW
Phase	3.0 ~

#### Mechanical - Output Details

Amplitude at air	2.500 mm
Vibrations	12,000.0 1/min
Vibrations (Hz)	200.0 Hz

#### Mechanical Details

Length Hose	0.8 m
-------------	-------

Weight	12.10 kg
Rubber cap	yes

#### Motor

Motor type	Asynchronous motor
------------	--------------------

#### Environment Data

Protection class	I / Protective earthing
Degree of protection	IP67

#### Electrical System

Breaker Switch On/Off	Yes
Integrated transformer	No
Length Cable	8.0 m
Kind of plug	CEE-Plug 4P 16A 250V 10H