



## LTT4

### Light Tower

#### Powerful and Compact

The LTT4 and LTT6 light towers offer a smaller footprint and the long-lasting LED's deliver exceptional light coverage for a variety of applications where temporary lighting is needed. The units are equipped with auxiliary power which adds to the versatility of these machines.

## Highlights

- LED Lights
- Programmable Controller
- Compact Design
- Standard Auxiliary Power
- Telescopic Vertical Mast

## Technical Data

### ■ Mechanical Details

Length	100.9 "
Width	47.5 "
Height	100.3 "
Operating weight	1,499.1 lb
Mast height max.	23.0 Foot

### ■ Generator

Output frequency	60.0 Hz
Voltage accuracy	10.0 %
Generator Rating 1~ (Continuous)	4.5 KW
Generator Manufacturer	Mecc Alte

### ■ Engine

Cooling	Water-cooling
Engine type	Diesel engine

Cylinder	2.0
Cylinder capacity	41.9 Inch <sup>3</sup>
Fuel	Winter Blend Diesel No. 2
Tank capacity	52.4 gal US
Effective power	7.4 hp
Operating Engine speed	1,800.0 1/min
Exhaust-gas limit	EPA Tier 4 final
Engine Manufacturer	Kohler

### ■ Electrical System

Lighting appliances	320W (LED)
Bulb power	320.0 W

### ■ Operating Fluids

Fuel consumption (Lights only)	0.2 GPH US
Run Time (Lights only)	211.1 hrs