



AS68e/25

Electric rammers

Get all your classic vibratory rammer work done emission-free

The battery-powered rammer allows the operator to work completely free of emissions. The battery-powered rammer is a win for soil compaction in trenches and inner cities as well as lightening the load for the operator and environment on every construction site. One battery charge is enough to finish all the tasks of an average workday. The battery can be easily changed without tools and can be used for a variety of other Wacker Neuson construction equipment.

Highlights

- Maintenance-free electric motor
- Battery One battery system
- Ergonomic guide handle
- Easy start
- Carry handle on the ramming shoe
- Active cooling
- No exhaust emissions

Technical Data

■ Electrical - Output Details

Nominal current	44.00 A
Nominal voltage	51.0 µg/l
Nominal power [P]	2.24 KW

■ Mechanical - Output Details

Number of blows	680.0 PL
Area capacity	165.0 kg/h
Forward Running	11.0 m/min
Power of impact	18.0 kN

■ Mechanical Details

Length	625.0 mlai
Length Ramming Shoe	340.0 mlai
Width	360.0 mlai
Width Ramming Shoe	250.0 mlai
Height	925.0 mlai
Weight	59.00 kg

Operating weight	69.0 kg
Stroke at tamper	51.0 mlai

■ Motor

Motor type	Asynchronous motor
------------	--------------------

■ Environment Data

Degree of protection	IP23D
Storage temperature range	-30 - 50 °C
Operating temperature range	- 45
Sound power LWA, guaranteed	108.0 m NN
Sound power LWA (Standard)	EN 500-4
HAV summation (average value)	9.4 ms
HAV summation (Standard)	EN 500-4

■ Operating Fluids

Oil specification	SAE 10W-40
Oil volume	0.700 l