

FUE10/042/200

Stationary frequency converters

Safety and output for long-term application

When it comes to safety and high output during long-term application there is no compromise with these electronic frequency converters. Besides, they are very sturdy and maintenance-free. Their high-quality components and the all-round housing offer protection against shocks, impacts and water.

Highlights

- Completely maintenance-free
- Secure protection

Technical Data

Electrical - Output Details

Nominal current	24.50 A
Nominal voltage	400.0 - 415.0 V
Nominal frequency	50.0 - 60.0 Hz
Output current	145.0 A
Output voltage	42.0 V
Output frequency	0.0 - 200.0 Hz
Phase	3.0 ~
Output Phase	3.0 ~

Mechanical Details

Length	500.0 mm
Width	500.0 mm
Height	550.0 mm
Weight	87.00 kg

Environment Data

Protection class	I / Protective earthing
Degree of protection	IP54

Electrical System

Breaker Switch On/Off	Yes
Operating indicator	yes
Adjusting frequency	yes
Length Cable	2.5 m
Kind of plug	CEE-Plug 5P 32A 400V 6H

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com