



## FUE10/042/200

### Stationary frequency converters

Safety and output for long-term application

When it comes to safety and high output during long-term application there is no compromise with these electronic frequency converters. Besides, they are very sturdy and maintenance-free. Their high-quality components and the all-round housing offer protection against shocks, impacts and water.

### Highlights

- Completely maintenance-free
- Secure protection

### Technical Data

#### ■ Electrical - Output Details

Nominal current	24.50 A
Nominal voltage	400.0 - 415.0 V
Nominal frequency	50.0 - 60.0 Hz
Output current	145.0 A
Output voltage	42.0 V
Output frequency	0.0 - 200.0 Hz
Phase	3.0 ~
Output Phase	3.0 ~

#### ■ Mechanical Details

Length	500.0 mm
Width	500.0 mm

Height	550.0 mm
Weight	87.00 kg

#### ■ Environment Data

Protection class	<input type="checkbox"/> I / Protective earthing
Degree of protection	<input type="checkbox"/> IP54

#### ■ Electrical System

Breaker Switch On/Off	<input type="checkbox"/> Yes
Operating indicator	<input type="checkbox"/> yes
Adjusting frequency	<input type="checkbox"/> yes
Length Cable	2.5 m
Kind of plug	<input type="checkbox"/> CEE-Plug 5P 32A 400V 6H