



PG2A

Dewatering Pumps of the PG series

Clear water from your job site or swimming pool quickly with Wacker Neuson dewatering pump.

With its self-priming centrifugal pumping action and overall compact size, the pump is ideal for the contractor with the need for temporary water removal.

Highlights

- Pump out vanes on back of impeller.
- Cast iron impeller and volute for long life and minimal service
- Carbon ceramic mechanical seal

Technical Data

Mechanical - Output Details

Flow rate max.	598.0 l/min
Solid diameter max.	6.5 mm
Suction head max.	7.6 m
Delivery height max.	30.0 m

Mechanical Details

Length	481.0 mm
Width	377.0 mm
Height	394.0 mm
Operating weight	24.0 kg
Intake-/Pressure socket-dia.	50.0 mm

Engine

Cooling	air cooling
---------	-------------

Engine type	Gasoline engine
Cylinder	1.0
Cylinder capacity	118.0 cm ³
Fuel	Gasoline
Fuel consumption	1.3 L/hr
Tank capacity	2.5 l
Oil filling max.	0.6 l
Power rating max.	2.6 KW
Engine speed (Power max.)	3,600.0 1/min
Operating Engine speed	3,600.0 1/min
Engine Manufacturer	Honda
Fuel consumption at full power	1.3 L/hr
Running time at 100%	1.9 hrs