



DPU40Yeh EU

Medium-weight reversible vibratory plates

Unbeatable on any surface

The medium-weight reversible vibratory plates offer high productivity as a result of its high compaction force in combination with fast forward and reverse travel speeds. They are the all-rounders for all construction sites where high demands are placed on the performance efficiency of a unit. In addition, they offer excellent characteristics in terms of long service life and operating comfort. Optimal application areas are the compaction of frost layers and subbases in street, path and parking lot construction as well as backfilling around buildings. Due to the frequency of 69 Hz, the medium-weight reversible vibratory plates are versatile for many jobs including the compaction over medium and heavy interlocking paving stones.

Highlights

- Sturdy and durable
- Very good accessibility to all maintenance points
- High surface performance

Technical Data

■ Mechanical - Output Details

| | |
|-------------------|-------------------------|
| Centrifugal force | 40 kN |
| Area capacity | 870.0 m ² /h |
| Forward Running | 24.0 m/min |
| Gradeability | 36.4 % |
| Vibrations (Hz) | 69.0 Hz |

Height Cover frame 725.0 mm

Thickness Baseplate 12.0 mm

Operating weight 383.0 kg

Underclearance 764.0 - 859.0 mm

■ Engine

Effective power 4.5 KW

Nominal Engine speed 3,000.0 1/min

■ Environment Data

HAV summation (Standard) EN 500-4

■ Operating Fluids

Cooling fluid type 0

■ Mechanical Details

| | |
|------------------|------------|
| Length Baseplate | 900.0 mm |
| Width | 604.0 mm |
| Width Baseplate | 440.0 mm |
| Height | 1,308.0 mm |

Available engines

Yanmar L70V

| | |
|----------------------------|---------------------|
| Cooling | air cooling |
| Engine type | Diesel engine |
| Engine operating mode | four-stroke |
| Cylinder | 1 |
| Cylinder capacity | 320 cm ³ |
| Fuel | Diesel EN 590 |
| Fuel consumption | 1.40 L/hr |
| Tank capacity | 3.30 l |
| Effective power | 4.50 KW |
| Nominal Engine speed | 3,000 PL |
| Standard (Effective power) | ISO 3046 IFN |
| Operating power | 4.3 KW |
| Operating Engine speed | 3,000 PL |
| Starter type | E-starter |
| Engine Manufacturer | Yanmar |