



RD24-100c DPF

Tandem roller

Convenient and efficient

The RD24 is the compact, versatile roller for every construction site. With its three-point articulated pendulum joint, the roller achieves a consistently even weight distribution with optimum maneuverability and travel stability. As a result, excellent, high-quality asphalt surfaces can be achieved. The user benefits from intuitive operation as well as the comprehensive view of the compaction area. Because of its compact dimensions, the RD24 is an excellent choice for use in confined areas.

Highlights

- Combination roller: Rear axle with rubber tires
- Uniform operating concept
- Large line-of-sight, compact construction

Technical Data

■ Mechanical - Output Details

Gradeability	30.0 %
Gradeability max. (without vibration)	40.0 %
Travel speed	0.0 - 10.2 km/h
Static linear load (front)	1.21 kg/mm
Compaction force Level I (front)	48 kN
Compaction force Level II (front)	34 kN
Vibration frequency Level I (front)	65.0 Hz
Vibration frequency Level II (front)	51.0 Hz
Amplitude Level I (front)	0.4500 mm
Amplitude Level II (front)	0.4500 mm
Centrifugal force Level I (front)	43 kN

■ Mechanical Details

Length	2,530.0 mm
Width	1,110.0 mm
Height	1,752.0 mm
Operating weight	2,385.0 kg
Dry Weight	2,190.0 kg
Gross vehicular weight	2,510.0 kg
Curb clearance right	55.0 mm
Curb clearance left	55.0 mm
Operating width	1,000.0 mm
Ground clearance	280.0 mm

Turning radius inside	2,470.0 mm
Operating weight with roll-over protective structure	2,385.0 kg
Wheelbase	1,700.0 mm
Operating weight, max.	3,110.00 kg
Curb clearance (left)	570.0 mm
Curb clearance (right)	570.0 mm
Empty weight with ROPS	2,190.0 kg
Turning radius outside	3,470.0 mm

■ Engine

Cylinder capacity	1,826.0 cm ³
Effective power	24.0 KW
Nominal Engine speed	2,200.0 1/min
Standard (Effective power)	ISO 14396
Starter battery Voltage	12.0 V
Battery capacity (nom. value)	95.0 Ah
Engine Manufacturer	Kubota
Engine Designation	D1803-CR

■ Environment Data

Sound level LpA	86.0 dB(A)
Sound power LWA, measured	102.0 dB(A)
Sound power LWA, guaranteed	106.0 dB(A)
Exhaust aftertreatment	DOC-DPF
Catalyst	yes

Particle filter	yes
CO (NRTC)	0.1 g/KWh
CO2 (NRTC)	858.7 g/KWh
HC + NOx (NRTC)	3.2 g/KWh
PM (NRTC)	0.0 g/KWh

■ Operating Fluids

Water tank capacity	180.0 l
---------------------	---------

Fuel Tank capacity	42.0 l
--------------------	--------

■ Chassis

Pendulum angle +/-	8.0 °
Width over tires (rear)	1,000.0 mm
Number of tires (rear)	4.0
Wheel size (rear)	205/60-R16
Wheel load per tire (rear)	293.8 kg