



EW65

Wheeled Excavator

power and speed

With a Wacker Neuson EW65 wheeled excavator, an operator can easily jump in the cab and head to the job site. The machine's road travel mode helps reduce time- and cost-intensive transport, while the variable drive system has a low rate of fuel consumption. With just one pedal to operate, the EW65 drives almost like a car. But it's a highly capable excavator, too. The powerful load-sensing hydraulic system (LUDV) ensures the same speed for several boom movements with different loads. With proportional control auxiliary hydraulics and a triple boom, the EW65 offers smooth work with attachments and an excellent digging range.

Highlights

- 3-point kinematics
- Intuitive operating concept
- Optimal positioning of hydraulic components
- Powerful drive system with LUDV
- Triple boom

Technical Data

Hydraulic		Inclined position max.	30.0 °
Operating pressure hydraulics	240.0 bar	Fuel	HVO EN15940
Flow rate	144.0 l/min	Effective power	45.5 KW
Tank capacity	92.0	Nominal Engine speed	3,000.0 1/min
Mechanical - Output Details		Operating power	45.5 KW
Nominal rotation speed	2,500.0 1/min	Operating Engine speed	3,000.0 1/min
Travel speed	30.0 km/h	Maximum torque	190.0 Nm
Mechanical Details		Air cleaner	Dry air filter
Length	6,349.0 mm	Battery capacity (nom. value)	88.0 Ah
Width	2,088.0 mm	Engine Manufacturer	Perkins
Height	2,775.0 mm	Environment Data	
Operating weight (minmax.)	6,755.0 - 8,647.0 kg	Sound power LWA, guaranteed	96.0 dB(A)
Digging depth (max.)	3,895.0 mm	Chassis	
Engine		Operating pressure	420.0 bar
Cooling	Water-cooling	Flow rate	144.0 l/min
Engine type	Diesel engine	Shipping and Storage	
Cylinder	4.0	Shipping weight	6,471.7 kg
Cylinder capacity	2,216.0 cm3		

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Available engines

56 kW Diesel engine (Stage 5)

Cooling	Water-cooling
Engine type	Diesel engine
Cylinder	4
Cylinder capacity	2,216 cm3
Fuel	Diesel EN 590
Effective power	43.5 KW
Nominal Engine speed	2,000 1/min
Engine speed (max. torque)	1,800 1/min
Exhaust-gas limit	EPA Tier 4 final, EU StageIIIB
Starter battery Voltage	12 µg/l
Engine Manufacturer	Perkins
Engine Designation	404F-E22TA
Stroke	100 mlai
Bore	84 mlai

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Dimensions



A1	Height with cab	2,775 mm
	Height of dozer blade	429 mm
A2	Total height with rotating beacon	2,952 mm
В	Width of upper carriage	1,931 mm
	Width of cab	1,000 mm
В	Width travel gear twin tires	2,088 mm
	Width travel gear single tires	1,931 mm
С	Transport length short shovel arm	6,114 mm
	Transport length long shovel arm	6,250 mm
D	Digging depth max., short shovel arm	3,531 mm
	Digging depth max., long shovel arm	3,831 mm
Е	Piercing depth max., short shovel arm	2,088 mm
	Piercing depth max., long shovel arm	2,361 mm
F	Piercing height max., short shovel arm	6,068 mm
G	Dumping height max., short shovel arm	4,207 mm
	Dumping height max., long shovel arm	4,389 mm
Н	Digging radius max., short shovel arm	6,220 mm
	Digging radius max., long shovel arm	6,504 mm
I	Max. reach at ground level (short shovel arm)	6,024 mm
	Max. reach at ground level (long shovel arm)	6,318 mm
J	Tail swing radius	1,459 mm
K1	Boom offset max. (to center of bucket right side)	766 mm
K2	Boom offset max. (to center of bucket left side)	492 mm
L	Stacking height max. (dozer blade above surface)	395 mm
М	Digging depth max. (dozer blade below surface)	301 mm
Ν	Length travel drive	2,887 mm
01	Max. swivel angle (arm system to the left)	67 °
O2	Max. swivel angle (arm system to the right)	63 °
	Track width	300 mm
	Boom swing radius center	2,465 mm
Q2	Boom swing radius right	2,393 mm
Q3	Boom swing radius left	1,940 mm
	Distance bucket dozer blade, short shovel arm	51 mm

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.