



**WACKER  
NEUSON**  
*all it takes!*



## AP1850we

### Single direction vibratory plate

Maneuverable on soil and asphalt,  
completely emission-free

With the Wacker Neuson battery-powered plate, the operator can perform soil and asphalt compaction work totally free from emissions. The battery-powered plates are ideal for working in trenches and inner cities, while being more environmentally friendly for the operator and the job site. With a battery runtime sufficient for a full day's work, the AP series opens up new areas of application while providing the same compaction performance results as conventional gas powered machines. The battery can be easily exchanged with a few easy steps and can be used in all Wacker Neuson battery-powered products.

### Highlights

- Starts with a push of a button
- Maintenance-free electric motor
- No exhaust emissions
- Low energy costs
- Removable battery

### Technical Data

#### ■ Mechanical - Output Details

Centrifugal force	18 kN
Area capacity	810.0 m <sup>2</sup> /h
Forward Running	27.0 m/min
Gradeability	46.6 %
Vibrations (Hz)	98.0 Hz

#### ■ Mechanical Details

Length Baseplate	600.0 mm
Width	500.0 mm
Width Baseplate	500.0 mm

Height	579.0 mm
Height Cover frame	482.0 mm
Thickness Baseplate	8.0 mm
Operating weight	107.0 kg
Ground clearance	579.0 mm

#### ■ Environment Data

Operating temperature range	0
HAV summation (average value)	4.0 m/s <sup>2</sup>
HAV summation (Standard)	EN 500-4