



## PS2 500

### Submersible Pump

These high performance single-phase submersible pumps are ideal for job sites needing fast, dependable, low level water pumping.

Pump can start in low water levels when it is primed through the discharge port. No matter how large or small the job. Wacker Neuson submersible pumps offer the versatility and durability contractors need for light dewatering. Suitable for most outlets, these pumps offer big pump features for small pump investment.

### Highlights

- Top discharge for continuous operation and motor cooling
- Built-in thermal protection prevents motor damage
- Durable mechanical seals
- Heavy-duty strain relief power cord
- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

### Technical Data

#### ■ Mechanical - Output Details

Flow rate max.	62.3 gal/mi
Solid diameter max.	0.2 "
Delivery height max.	39.4 Foot

#### ■ Mechanical Details

Length	7.3 "
Width	7.3 "
Height	12.0 "
Operating weight	20.9 lb

#### ■ Motor

Nominal power	0.48 KW
---------------	---------

Nominal current	3.0 A
Nominal voltage	220.0 V
Nominal frequency	60.0 Hz
Nominal speed	3,270.0 1/min

#### ■ Electrical System

Length Cable	32.8 Foot
--------------	-----------

#### ■ Shipping and Storage

Length for shipping	13.7 "
Width for shipping	9.8 "
Height for shipping	9.0 "
Shipping weight	28.0 lb