



**WACKER
NEUSON**
all it takes!

BPS1550c

Single-direction vibratory plates

Easy to maneuver and high performance

These Wacker Neuson vibratory plates offer functionality and performance at a real value price. The compact design allows for compaction of mixed soils in the smallest spaces even in extremely narrow trenches. The guide handle with vibration damping results in longer working hours and less fatigue for the operator.

Highlights

- Reliable Loncin engine
- Durable and maintenance free compaction system
- Big water tank
- Ergonomic and comfort designed handle
- Easy lifting and transport

Technical Data

■ Mechanical - Output Details

Centrifugal force	15 kN
Vibrations	5,460.0 - 5,700.0 1/min
Transmission	• Centrifugal Clutch - V-belt
Area capacity	750.0 m²/h
Forward Running	20.0 - 25.0 m/min
Gradeability	30.0 %
Vibrations (Hz)	91.0 - 95.0 Hz

■ Mechanical Details

Length Baseplate	615.0 mm
Width	500.0 mm
Width Baseplate	500.0 mm
Height	950.0 mm
Thickness Baseplate	14.0 mm
Thickness Baseplate min.	11.0 mm

Operating weight	87.0 kg
------------------	---------

■ Engine

Effective power	4.4 kW
Nominal Engine speed	3,600.0 1/min

■ Environment Data

Storage temperature range	-15 - 40 °C
Operating temperature range	-15 - 45 °C
Sound power LWA, guaranteed	108.0 dB(A)
Sound power LWA (Standard)	• EN 500-4, 2000/14/EG
Vibration total value ahv	5.8 m/s²
Vibration value ahv (Standard)	• EN 500-4

■ Operating Fluids

Water tank capacity	10.0 l
Exciter oil volume	0.20 l
Fuel consumption	0.9 l/h