



E12540B

Hydronic Heater

easy to transport, simple to use hydronic heater.

The E 1250 was designed with the safety features you require and the simple, intelligent operation you desire. All operator interface points are conveniently located in the rear of the machine for simplified operation. Our new concrete cure mode simplifies the guesswork in maintaining proper concrete temperature, and our user-friendly control panel incorporates a watchdog circuit, E-Stop, and single point reset for the most common faults. All versions are telematics ready.

Highlights

- Powerful positive displacement pumps

Technical Data

■ Electrical - Output Details

Nominal current	15.00 A
Nominal voltage	120.0 V

■ Mechanical Details

Length	140.0 "
Gross Axle Weight Rating	3,999.2 lb
Width	76.0 "
Height	68.0 "
Operating weight	3,174.7 lb
Dry Weight	2,729.3 lb
Gross vehicular weight	3,174.7 lb
Lift Bail - quantity	0.0
Length hose	1,250.0 Foot

■ Generator

Genset	no
--------	----

■ Environment Data

Operating temperature range	100 - 199 °F
Sound level LpA	64.5 dB(A)

■ Electrical System

Temperature monitor	digital
---------------------	---------

Display Equipment

Performance monitoring light

■ Operating Fluids

Fuel specification	Winter Blend Diesel No. 2
Run Time (75 % Prime Load)	90.0 hrs
Fuel Tank capacity	71.1 gal US
Utilizable tank capacity	68.2 gal US
Fuel Consumption no genset	1.0 GPH US
Fuel Consumption Natural Gas	17.5 gal/mi
Fuel Consumption Propane	1.5 GPH US
Run Time (100 %)	68.0 hrs

■ Chassis

Brake	Electric brake
Hitch Type	Centrifugal Clutch
Tongue Weight, min.	169.8 lb
Tongue Weight, max.	229.3 lb
Tires	ST205/75R15

■ Shipping and Storage

Shipping weight	2,729.3 lb
Shipping weight with Trailer	2,729.3 lb