



# IRFU45/120/5 UK

## **High-frequency internal vibrators**

Top Performance from every model

The IRFU high-frequency internal vibrator series are easy to use. They simply connect to the single-phase power supply and are ready to use. They offer reliable operation even when used with fluctuating generator input voltages. The Wacker Neuson IRFU high-performance internal vibrator is designed for long life and professional concrete consolidation results. It is available in many different versions. The integrated personal protection switch (Bodyguard<sup>™</sup>) offers a high standard of safety.

### Highlights

- Bodyguard
- Completely tempered vibrator head
- Thermal overload protection breaker
- High-performance electric motor with stable speeds
- Switch box with integrated frequency converter

#### **Technical Data**

#### Electrical - Output Details

•	
Nominal current	9.60 A
Nominal voltage	110.0 - 130.0 V
Nominal frequency	50.0 - 60.0 Hz
Nominal power [P]	0.88 KW
Phase	1.0 ~
Mechanical - Output Details	
Amplitude at air	2.300 mm
Vibrations	12,000.0 1/min
Vibrations (Hz)	200.0 Hz
Mechanical Details	
Length Hose	5.0 m

Weight	17.00 kg
Rubber cap	no
Motor	
Motor type	Asynchronous motor
Environment Data	
Protection class	I / Protective earthing
Degree of protection	IP67
Electrical System	
Breaker Switch On/Off	Yes
Intograted transformer	
Integrated transformer	yes
Length Cable	yes 15.0 m

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.