



**WACKER  
NEUSON**  
*all it takes!*

## PS2-3703

### Submersible Pump

powerful and reliable for construction site dewatering

The robust PS series three-phase submersible pumps can handle wastewater containing solids up to a diameter of 20 mm. They feature a high flow rates and high heads, making them ideal for applications where it is important to dry out construction sites quickly and reliably. These high-quality pumps are extremely durable and easy to use. The PS series are also offered in lightweight aluminum models and automatic versions.

### Highlights

- Model variations
- Optional motor protection plug for three-phase pumps
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Oil lifter for reliable lubrication in any situation
- Safe to run dry
- Steel sleeve reduces wear of the shaft

### Technical Data

#### ■ Electrical - Output Details

|                               |         |
|-------------------------------|---------|
| Nominal voltage               | 400.0 V |
| Nominal frequency             | 50.0 Hz |
| Starting current Idle running | 58.0 A  |
| Starting current full load    | 7.5 A   |
| Phase                         | 3.0 ~   |

#### ■ Mechanical - Output Details

|                      |             |
|----------------------|-------------|
| Flow rate max.       | 450.0 l/min |
| Solid diameter max.  | 8.5 mm      |
| Delivery height max. | 36.5 m      |

#### ■ Mechanical Details

|                              |          |
|------------------------------|----------|
| Length                       | 285.0 mm |
| Width                        | 250.0 mm |
| Height                       | 655.0 mm |
| Operating weight             | 55.0 kg  |
| Intake-/Pressure socket-dia. | 50.0 mm  |

#### ■ Motor

|               |               |
|---------------|---------------|
| Nominal speed | 2,850.0 1/min |
|---------------|---------------|

#### ■ Electrical System

|                     |                     |
|---------------------|---------------------|
| Length Cable        | 20.0 m              |
| Cable cross-section | 1.5 mm <sup>2</sup> |