



AR 34/3/400

External vibrator

The expert for bulk material

Wacker Neuson external vibrators deliver excellent results when filling, consolidating, transporting and sifting bulk material Its maximum 3,000 rpm ensures that bulk material is moving continuously, does not clump and is thus optimally prepared for later use. There are a variety sizes and versions of Wacker Neuson external vibrators for loosening, separating and transporting.

Highlights

- Asynchronous motor with stable speed
- Adjustable eccentric weight discs

Technical Data

Electrical - Output Details		Height	134.0 mm
Nominal current	0.75 A	Weight	7.00 kg
Nominal voltage	400.0 V	Unbalanced mass/side pos1	32.0
Nominal frequency	50.0 Hz	Unbalanced mass/side pos2	0.0
Nominal power [P]	0.40 KW	Motor	
Phase	3.0 ~	Motor type	Asynchronous motor
Mechanical - Output Details		Environment Data	
Centrifugal force	3 kN	Protection class	I / Protective earthing
Vibrations	3,000.0 1/min	Degree of protection	IP67
Vibrations (Hz)	50.0 Hz	Electrical System	
Centrifugal force max.	3.47 kN	Breaker Switch On/Off	no
Mechanical Details		Operating indicator	No
Length	295.0 mm	Adjusting frequency	No
Width	151.0 mm	Integrated transformer	No

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.