



PSA2 800

Submersible Pump

Automatic, lightweight pumps, perfect for any task

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Highlights

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

■ Mechanical - Output Details

Flow rate max.	310.0 l/min
Solid diameter max.	6.0 mm
Delivery height max.	18.0 m

Nominal frequency 60.0 Hz

Nominal speed 3,300.0 1/min

■ Mechanical Details

Length	192.0 mm
Width	223.0 mm
Height	341.0 mm
Operating weight	13.8 kg
Intake-/Pressure socket-dia.	50.0 mm

Nominal frequency 60.0 Hz

Nominal speed 3,300.0 1/min

■ Environment Data

Temperature limit borrowed liquid 40.0 °C

■ Electrical System

Length Cable	15.0 m
Cable cross-section	2.0 mm ²
Cable definition	PVC Sheath

■ Shipping and Storage

Length for shipping	475.0 mm
Width for shipping	267.0 mm
Height for shipping	260.0 mm
Shipping weight	17.0 kg

■ Motor

Nominal power	0.75 KW
Nominal current	5.3 A
Nominal voltage	220.0 V