



**WACKER
NEUSON**
all it takes!

ARFU26/6/120 US

External vibrators for consolidation of in-situ concrete

For quality exposed concrete to satisfy high expectations

For the production of concrete surfaces, flawlessly consolidated concrete is essential. The high quality design of Wacker Neuson's AR26 with integrated frequency converter offers precision concrete consolidation. The result: beautifully smooth and level concrete surfaces on walls, pillars and columns.

Highlights

- Integrated converter
- Small, compact and light
- Asynchronous motor with stable speed
- Sturdy design

Technical Data

■ Electrical - Output Details

Nominal current	3.00 A
Nominal voltage	110.0 - 130.0 V
Nominal frequency	50.0 - 60.0 Hz
Nominal power [P]	0.28 KW
Phase	1.0 ~

■ Mechanical - Output Details

Centrifugal force	517 lbf
Vibrations	6,000.0 1/min
Vibrations (Hz)	100.0 Hz
Centrifugal force max.	780.09 lbf

■ Mechanical Details

Length	8.8 "
Width	7.5 "
Height	4.0 "

Weight	25.66 lb
Unbalanced mass/side pos1	6.0
Unbalanced mass/side pos2	2.0

■ Motor

Motor type	Asynchronous motor
------------	--------------------

■ Environment Data

Protection class	I / Protective earthing
Degree of protection	IP66

■ Electrical System

Breaker Switch On/Off	Yes
Operating indicator	yes
Adjusting frequency	No
Integrated transformer	yes
Length Cable	49.2 Foot
Kind of plug	NEMA 5-15P - 14W47