



PS2 500

Submersible Pump

These high performance single-phase submersible pumps are ideal for job sites needing fast, dependable, low level water pumping.

Pump can start in low water levels when it is primed through the discharge port. No matter how large or small the job. Wacker Neuson submersible pumps offer the versatility and durability contractors need for light dewatering. Suitable for most outlets, these pumps offer big pump features for small pump investment.

Highlights

- Top discharge for continuous operation and motor cooling
- Built-in thermal protection prevents motor damage
- Durable mechanical seals
- Heavy-duty strain relief power cord
- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

■ Mechanical - Output Details

Flow rate max.	236.0 l/min
Solid diameter max.	6.0 mm
Delivery height max.	12.0 m

Nominal current 3.0 A

Nominal voltage 220.0 V

Nominal frequency 60.0 Hz

Nominal speed 3,270.0 1/min

■ Mechanical Details

Length	186.0 mm
Width	186.0 mm
Height	304.0 mm
Operating weight	9.5 kg

■ Electrical System

Length Cable 10.0 m

■ Motor

Nominal power	0.48 KW
---------------	---------

Length for shipping 349.0 mm

Width for shipping 248.0 mm

Height for shipping 229.0 mm

Shipping weight 12.7 kg