



PS2 500 Submersible Pump

These high performance single-phase submersible pumps are ideal for job sites needing fast, dependable, low level water pumping.

Pump can start in low water levels when it is primed through the discharge port. No matter how large or small the job. Wacker Neuson submersible pumps offer the versatility and durability contractors need for light dewatering. Suitable for most outlets, these pumps offer big pump features for small pump investment.

Highlights

- Top discharge for continuous operation and motor cooling
- Built-in thermal protection prevents motor damage
- Durable mechanical seals
- Heavy-duty strain relief power cord
- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

■ Mechanical - Output Details

Flow rate max.	236.0 l/min
Solid diameter max.	6.0 mm
Delivery height max.	12.0 m

■ Mechanical Details

Length	186.0 mm
Width	186.0 mm
Height	304.0 mm
Operating weight	9.5 kg

■ Motor

Nominal power	0.48 KW
---------------	---------

Nominal current	3.0 A
Nominal voltage	220.0 V
Nominal frequency	60.0 Hz
Nominal speed	3,270.0 1/min

■ Electrical System

Length Cable	10.0 m
--------------	--------

■ Shipping and Storage

Length for shipping	349.0 mm
Width for shipping	248.0 mm
Height for shipping	229.0 mm
Shipping weight	12.7 kg