

LTT6

Light Tower

Powerful and Compact

The LTT4 and LTT6 light towers offer a smaller footprint and the long-lasting LED's deliver exceptional light coverage for a variety of applications where temporary lighting is needed. The units are equipped with auxiliary power which adds to the versatility of these machines.

Highlights

- LED Lights
- Programmable Controller
- Compact Design
- Standard Auxiliary Power
- Telescopic Vertical Mast

Technical Data

Mechanical Details

Length	2,563.0 mm
Width	1,207.0 mm
Height	2,548.0 mm
Operating weight	705.0 kg
Mast height max.	7.0 m

Generator

Output frequency	60.0 Hz
Voltage accuracy	10.0 %
Gen. Rating 1~ (Cont.) [kW]	6.0 kW
Generator Manufacturer	Mecc Alte

Engine

Cooling	Water-cooling
Engine type	Diesel engine
Cylinder	3.0
Cylinder capacity	1,028.0 cm³
Kraftstofftyp	Winter Blend Diesel No. 2
Tank capacity	198.4 l
Effective power	8.4 kW
Operating Engine speed	1,800.0 1/min
Exhaust-gas limit	EPA Tier 4 final
Engine Manufacturer	Kohler

Electrical System

Lighting appliances	320W (LED)
Bulb power	320.0 W

Operating Fluids

Fuel consumption (Lights only)	1.1 l/h
Run Time (Lights only)	173.4 hrs

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com