



LTT6

Light Tower

Powerful and Compact

The LTT4 and LTT6 light towers offer a smaller footprint and the long-lasting LED's deliver exceptional light coverage for a variety of applications where temporary lighting is needed. The units are equipped with auxiliary power which adds to the versatility of these machines.

Highlights

- LED Lights
- Programmable Controller
- Compact Design
- Standard Auxiliary Power
- Telescopic Vertical Mast

Technical Data

Mechanical Details

Length	2,563.0 mm
Width	1,207.0 mm
Height	2,548.0 mm
Operating weight	705.0 kg
Mast height max.	7.0 m

Generator

Output frequency	60.0 Hz
Voltage accuracy	10.0 %
Generator Rating 1~ (Continuous)	6.0 KW
Generator Manufacturer	• Mecc Alte

Engine

Cooling	• Water-cooling
Engine type	• Diesel engine

Cylinder	3.0
Cylinder capacity	1,028.0 cm ³
Fuel	• Winter Blend Diesel No. 2
Tank capacity	198.4 l
Effective power	8.4 KW
Operating Engine speed	1,800.0 1/min
Exhaust-gas limit	• EPA Tier 4 final
Engine Manufacturer	• Kohler

Electrical System

Lighting appliances	• 320W (LED)
Bulb power	320.0 W

Operating Fluids

Fuel consumption (Lights only)	1.1 L/hr
Run Time (Lights only)	173.4 hrs