



G130

Mobile Generator

Powerful prime power generator, suited for the toughest applications

The G130 is a durable, sound attenuated diesel generator that provides mobile prime power for larger construction, commercial, industrial, special event and emergency management applications where quiet, reliable power is needed. The digital controller monitors and protects the generator and engine. The standard environmentally friendly features include a 115% fluid containment, crankcase oil vapor recovery system, no mess oil and radiator drain hoses and fast fuel fill system that minimizes fuel spill potential.

Highlights

- Programmable Controller
- Cummins QSB5-G11 Engine
- Long Run Time
- Powerful and Precise Alternator
- 600 Volt Alternator

Technical Data

Generator

Insulation class	• H
Output current 1~	264.0 A
Voltage accuracy	1.0 %
Output current 3~	313.0 A
Generator Rating 1~ (Continuous)	75.0 kVA
Generator Rating 3~ (Continuous)	162.0 kVA
Generator Manufacturer	• Mecc Alte
Generator specification	• AVR without Brushes
Voltage 1~	240.0 V
Voltage 3~	480.0 V

Engine

Engine type	• Diesel engine
Engine operating mode	• four-stroke
Cylinder	4.0
Cylinder capacity	274.6 Inch ³
Fuel	• Diesel EN 590
Exhaust-gas limit	• IIIB/Tier IV Final
Starter battery Voltage	24.0 V
Battery Cold-start current CCA	950.0 A

Engine Manufacturer	• Cummins
---------------------	-----------

Operating Fluids

Cooling fluid volume	45.4 qt US
Tank capacity AdBlue® / DEF	69.7 pt US
Consumption AdBlue®/DEF (Prime Load)	0.3 GPH US
Run Time AdBlue®/DEF (Prime Load)	25.6 hrs
Fuel consumption (Prime load)	7.1 GPH US
Run Time (Prime Load)	24.6 hrs
Run Time (75 % Prime Load)	32.5 hrs
Run Time (50 % Prime Load)	46.5 hrs

Shipping and Storage

Length for shipping	113.0 in
Width for shipping	47.5 in
Height for shipping	78.5 in
Shipping weight	5,471.9 lb
Shipping weight with Trailer	6,655.8 lb
Length for shipping (with Trailer)	176.0 in
Width for shipping (with Trailer)	80.0 in
Height for shipping (with Trailer)	91.8 in