



WPU1550Aw

Reversible vibratory plate

Wacker Neuson's smallest reversible

The WPU1550 reversible vibratory plate is a powerful machine for confined area compaction of asphalt, interlocking paving stones and mixed soils. The heavy-duty design is ideally suited for continuous professional use in gardening and landscaping applications as well as compacting gravel, and sand for road construction, walkways, along foundations and parking lots. Using the integrated wheel set, the WPU1550 can be easily moved onto and around the job site, even on hot asphalt.

Highlights

- Optimally shaped base plate
- Integrated transport roller
- Sturdy protective frame for engine and water tank
- Base plate made of nodular cast iron (GJS700)
- Honda gasoline engine

Technical Data

| Mechanical - Output Details | | Engine | |
|-----------------------------|------------|--------------------------------|----------------------|
| Centrifugal force | 15 kN | Effective power | 3.6 KW |
| Area capacity | 810.0 m2/h | Nominal Engine speed | 3,600.0 1/min |
| Forward Running | 27.0 m/min | Environment Data | |
| Backward Running | 20.0 m/min | Sound level LpA | 93.6 dB(A) |
| Gradeability | 30.0 % | Sound level LpA (Standard) | EN 500-4 |
| Vibrations (Hz) | 97.0 Hz | Sound power LWA, measured | 105.3 dB(A) |
| Mechanical Details | | Sound power LWA, guaranteed | 108.0 dB(A) |
| Length Drawbar op. pos. | 1,012.0 mm | Sound power LWA (Standard) | EN 500-4, 2000/14/EG |
| Length Baseplate | 586.0 mm | Vibration total value ahv | 5.8 m/s2 |
| Width | 500.0 mm | Vibration value ahv (Standard) | EN 500-4 |
| Width Baseplate | 500.0 mm | Operating Fluids | |
| Height | 586.0 mm | Water tank capacity | 12.0 l |
| Operating weight | 105.0 kg | Exciter oil volume | 0.18 |

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Available engines

GX160UH2X SWX2

| Cooling | air cooling |
|----------------------------|-----------------|
| Engine type | Gasoline engine |
| Engine operating mode | four-stroke |
| Cylinder | 1 |
| Cylinder capacity | 163 cm3 |
| Inclined position max. | 20 cos φ |
| Fuel | Gasoline |
| Fuel management | Carburettor |
| Tank capacity | 3.11 |
| Oil filling max. | 0.6 |
| Power rating max. | 3.6 KW |
| Engine speed (Power max.) | 3,600 PL |
| Standard (Power max.) | SAE J1349 |
| Maximum torque | 10.3 l/h |
| Engine speed (max. torque) | 2.500 PL |
| Spark plug(s) | NGK BPR-6 ES |
| Electrode distance | 0.70 mlai |
| Air cleaner | Dry air filter |
| Starter type | Recoil starter |