

PT6LT

Self Priming Trash Pump

Tough trash pumps great for a variety of applications

PT pumps are ideal for general dewatering of excavations, flooded basements, manholes, utility vaults, mining work, swimming pools, lakes and barge holds or wherever there is unwanted water. With built-in contractor friendly features, this line of trash pumps has redefined the quality and durability standards of self-priming, centrifugal trash pumps.

Highlights

- Proven Yanmar engine
- Ductile iron pump housing

Technical Data

Mechanical - Output Details

Flow rate max.	4,933.0 l/min
Pump pressure max.	2.6 bar
Solid diameter max.	50.0 mm
Suction head max.	7.5 m
Delivery height max.	30.5 m

Mechanical Details

Length	2,721.0 mm
Width	1,596.0 mm
Height	1,660.0 mm
Operating weight	950.0 kg
Intake-/Pressure socket-dia.	152.0 mm

Engine

Tank capacity	90.0 l
Engine speed 1	2,700.0 1/min
Fuel consumption at Engine speed 1	5.1 l/h
Run Time at Engine speed 1	17.5 hrs

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com