

AR52/9/042

External vibrators for consolidation of prefabricated concrete factories

For 24-hour continuous application

Count on the durability and long service life of this external vibrator: it performs with maximum reliability and safety in the toughest operating conditions. Even when operating in a 24-hour application This is due to the low vibration and heat-resistant windings of the electric motor (plastic casing, Class H up to 180°C) as well as the extremely robust special bearings. That gives you two more advantages: long service life and minimum maintenance requirements.

Highlights

- Sturdy design

Technical Data

Electrical - Output Details

Nominal current	14.00 A
Nominal voltage	42.0 V
Nominal frequency	150.0 Hz
Nominal power [P]	0.80 kW
Phase	3.0 ~

Mechanical - Output Details

Centrifugal force	9 kN
Vibrations	9,000.0 1/min
Vibrations (Hz)	150.0 Hz
Centrifugal force max.	13.77 kN

Mechanical Details

Length	231.0 mm
Width	217.0 mm
Height	204.0 mm
Weight	17.90 kg
Unbalanced mass/side pos1	3.0
Unbalanced mass/side pos2	1.0
Hole pattern length	120.0 mm
Hole pattern width	120.0 mm
Hole pattern hole diameter	17.0 mm

Motor

Motor type	Asynchronous motor

Environment Data

Protection class	III / Safety extra-low voltage
Degree of protection	IP67

Electrical System

Breaker Switch On/Off	no
Operating indicator	No
Adjusting frequency	No
Integrated transformer	No

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Copyright © 2026 Wacker Neuson SE | www.wackerneuson.com