



## GS8003G

### Portable Generator of the G series

Reliable power solutions for demanding use

The G Series generators are engineered to meet the demands of professional applications, offering high load starting, high power output, durability and cost-effectiveness. These generators feature with strong air filtration system and a large fuel tank, ensuring longer operation and superior reliability. With a robust frame, the G Series is built to withstand harsh environments and continuous use.

### Highlights

- Sturdy protective frame
- Large tank with long running time
- Reliable Loncin engine
- Automatic Voltage Regulation (AVR)
- Compact dimensions

### Technical Data

#### ■ Mechanical Details

Length	695.0 mm
Width	546.0 mm
Height	550.0 mm
Dry Weight	83.0 kg
<b>■ Generator</b>	
Insulation class	A
Output current 1~	10.9 A
Output frequency	50.0 Hz
Efficiency factor 1~	1.0 cos φ
Nominal speed	3,000.0 1/min
Efficiency factor 3~	0.8 cos φ
Phase	1.0 ~
Output current 3~	13.9 A
Generator Rating 1~ (Continuous)	2.5 KW
Generator specification	AVR with Brushes
Voltage 1~	230.0 V
Voltage 3~	400.0 V
Maximum Output	8,000.0 W

Continuous Output 7,700.0 W

#### ■ Engine

Tank capacity 30.0 l

#### ■ Environment Data

Degree of protection IP23

Sound power LWA, guaranteed 97.0 dB(A)

Sound power LWA (Standard) 2000/14/EG

#### ■ Electrical System

Circuit Breaker Amperage AC 13.0 A

Available voltages 1~ 230.0 V

Breaker Switch On/Off 1 Pole

CE Performance Class G1

Type of battery LiFePO4

Installed capacity 1.6 Ah

Receptacle Type CEE7/3 (Typ F) 2P 16A 250V, IP44 1~

#### ■ Operating Fluids

Fuel consumption (50 % Prime Load) 2.7 L/hr

Run Time (50 % Prime Load) 11.0 hrs