



PS3-1503

PS series (400 V, 3~) submersible trash-water pumps

powerful and reliable for construction site dewatering

The robust PS series three-phase submersible pumps can handle wastewater containing solids up to a diameter of 20 mm. They feature a high flow rates and high heads, making them ideal for applications where it is important to dry out construction sites quickly and reliably. These high-quality pumps are extremely durable and easy to use. The PS series are also offered in lightweight aluminum models and automatic versions.

Highlights

- Model variations
- Optional motor protection plug for three-phase pumps
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Oil lifter for reliable lubrication in any situation
- Safe to run dry
- Steel sleeve reduces wear of the shaft

Technical Data

■ Electrical - Output Details

Nominal current	3.50 A
Nominal voltage	400.0 V
Nominal frequency	50.0 Hz
Phase	3.0 ~

Width 215.0 mm

Height 550.0 mm

Operating weight 34.0 kg

Intake-/Pressure socket-dia. 75.0 mm

■ Motor

Nominal speed 2,850.0 1/min

■ Electrical System

Length Cable 20.0 m

Cable cross-section 1.5 mm²

■ Mechanical - Output Details

Flow rate max.	670.0 l/min
Solid diameter max.	8.5 mm
Delivery height max.	14.4 m

■ Motor

Nominal speed 2,850.0 1/min

■ Electrical System

Length Cable 20.0 m

Cable cross-section 1.5 mm²

■ Mechanical Details

Length	235.0 mm
--------	----------