



WL950

Wheel Loader

The top performer

These features characterise the WL950 wheel loader: Comfort cabin with excellent ergonomics and 360° visibility, electronically controlled drive system with various operating modes, sturdy load arm with an optimal view of the attachment, large range of options and a modern machine design. The transversely installed engine and the optimised arrangement of components ensure very good maintenance access. The WL950 is the ideal model in the wheel loader class with 0.85 m³ bucket volume. It combines power, reliable hydraulics and compact dimensions with well-engineered technology and an excellent price-performance ratio.

Highlights

- Comfortable Cab
- Perfectly matched Z-kinematics
- Robust central joint with optimized hose routing
- Motor installed transversely
- Service access front end

Technical Data

■ Standard engine data

Engine manufacturer	Kohler
Motor type	KDI1903TCR
Cylinder	3
Drive output	42 kW
Drive output	57 PS
at max. rpm	2,600 U/min
Maximum torque	225 Nm
Cylinder capacity	1,861 cm ³
Type of coolant	Water
Exhaust standard level	V
Exhaust aftertreatment	DOC/DPF

Tipping load with bucket – machine pivoted, loading frame horizontal 3,070 - 3,410 kg

Tipping load with pallet fork – machine straight, loading frame horizontal 2,960 - 3,260 kg

Tipping load with pallet fork – machine pivoted, loading frame horizontal 2,560 - 2,830 kg

■ Driver's cab

Driver's cab Cab

■ Filling levels

Tank capacity for fuel 80 l

Tank capacity for hydraulic oil 32 l

■ Drive system

Type of drive electronically controlled

drive unit Hydrostatic via transfer gearbox and universal joint shaft

Speed levels 2

Axle PA1422

Travel speed Standard 0-20 km/h

Operating brake Drum brake

Parking brake drum brake (mechanical handbrake lever)

Differential lock 100 % front axle + rear axle

■ Hydraulic system

Drive hydraulics working pressure (max.) 500 bar

■ Electrical system

Operating voltage	12 V
Battery	100 Ah
Alternator	120 A

■ Weights

Bucket capacity (standard bucket)	0.85 m ³
Operating weight	5,000 - 5,200 kg
Tipping load with bucket – machine straight, loading frame horizontal	3,570 - 3,950 kg

Work hydraulics discharge volume (max.)	74 l/min
Work hydraulics working pressure (max.)	235 bar

Steering cylinder 1

■ Noise characteristic values

Average sound power level LwA (cabin)	99.9 dB(A)
Guaranteed sound power level LwA (cabin)	101 dB(A)
Specified sound pressure level LpA (cabin)	69 dB(A)

■ Other information

DPF = diesel particulate filter
 DOC = diesel oxidation catalyst
 Tipping load calculation pursuant to ISO 14397

■ Kinematics


Kinematics type	Z
Lifting cylinder	1
Tipping cylinder	1

Quick change system hydraulic

■ Steering

Steering type	hydraulically activated articulated pendulum steering
---------------	---

Dimensions



A	Total length	5,430 mm
B	Total length without bucket	4,670 mm
C	Bucket pivot point (to center of axle)	960 mm
D	Wheel base	2,150 mm
E	Rear overhang	1,435 mm
F	Height with cab	2,510 mm
H	Seat height	1,485 mm
J	Total working height	4,070 mm
K	Bucket pivot point (max. lift height)	3,250 mm
L	Load-over height	2,995 mm
M	Dumping height	2,450 mm
N	Reach (at M)	675 mm
O	Digging depth	85 mm
P	Total width	1,830 mm
Q	Track width	1,420 mm
S	Ground clearance	375 mm
T	Maximum radius	4,300 mm
U	Radius on the outer edge	3,935 mm
V	Inner radius	2,070 mm
W	Articulation angle	40 °
X	Rollback angle at max. lift height	66 °
Y	Dumping angle	45 °
Z	Rollback angle on ground	44 °