



BH55rw 28x160

Gasoline breaker

The specialist for track construction

The BH55rw petrol hammer provides ideal conditions for use in track construction, because track ballast has to be processed again and again when maintaining the rail network. The tamping requires a rather gentle force, because the ballast may not be damaged during tamping. However, a certain percussion rate is required so that the ballast is properly compacted. The BH 55rw offers this combination. The "rw" ending here stands for "railway" and refers to the 1,350 blows per minute with 55 joules of single stroke impact energy. It is an ideal combination of percussion rate and power for the special requirements on the track.

Highlights

- High single stroke impact energy at a low weight
- Hood spring mounting
- Powerful, sturdy percussion system
- Stable, well-balanced handle

Technical Data

■ Mechanical - Output Details

| | |
|---------------------|---------------|
| Number of blows | 1,350.0 1/min |
| Singel beat energie | 55.0 J |

■ Mechanical Details

| | |
|---------------------|----------|
| Length without tool | 898.0 mm |
| Width without tool | 492.0 mm |
| Depth without tool | 346.0 mm |

| | |
|-------------|------------|
| Weight | 25.20 kg |
| Tool holder | Hex 28x160 |

■ Engine

| | |
|----------------------|---------------|
| Effective power | 1.6 KW |
| Nominal Engine speed | 4,500.0 1/min |

■ Operating Fluids

| | |
|-----------------------|--------|
| Lubrication intervall | 40.0 h |
|-----------------------|--------|